

SAFETY DATA SHEET

PROHESIVE ULTRAPRO



Version 1.0

SDS Number: 100000013073

Revision Date: 30.05.2016

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : PROHESIVE ULTRAPRO
Product code : 100000013073
Type of product : solid

Manufacturer or supplier's details


Company : Sika Australia Pty. Ltd.
Address : Elizabeth Street 55
Wetherill Park NSW 2164
Telephone : +61297251145
Emergency telephone number : + 61 1800 033 111
Telefax : +61297253330
E-mail address : EHS@au.sika.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation : Category 2
Serious eye damage/eye irritation : Category 1
Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

Precautionary statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.
Response:

SAFETY DATA SHEET
PROHESIVE ULTRAPRO



Version 1.0

SDS Number: 100000013073

Revision Date: 30.05.2016

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (%)
Cement, portland, chemicals	65997-15-1	>= 30 - < 60
glass, oxide, chemicals	65997-17-3	>= 10 - < 30
calcium carbonate	471-34-1	>= 10 - < 30
calcium sulfate	7778-18-9	< 10

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.
Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

SAFETY DATA SHEET
PROHESIVE ULTRAPRO



Version 1.0

SDS Number: 100000013073

Revision Date: 30.05.2016

Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.

Most important symptoms and effects, both acute and delayed : irritant effects
Cough
Respiratory disorder
Excessive lachrymation
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
Causes skin irritation.
Causes serious eye damage.
May cause respiratory irritation.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Hazardous combustion products : No hazardous combustion products are known

Specific extinguishing methods : Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Avoid breathing dust.
Deny access to unprotected persons.

Environmental precautions : Try to prevent the material from entering drains or water courses.

Methods and materials for containment and cleaning up : Pick up and arrange disposal without creating dust.
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.

Advice on safe handling : Do not breathe vapours/dust.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.

SAFETY DATA SHEET
PROHESIVE ULTRAPRO



Version 1.0

SDS Number: 100000013073

Revision Date: 30.05.2016

For personal protection see section 8.
 Smoking, eating and drinking should be prohibited in the application area.
 Follow standard hygiene measures when handling chemical products

- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
 When using do not eat or drink.
 When using do not smoke.
 Wash hands before breaks and at the end of workday.
- Conditions for safe storage : Store in original container.
 Keep in a well-ventilated place.
 Observe label precautions.
 Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Cement, portland, chemicals	65997-15-1	TWA	10 mg/m3	AU OEL
	Further information: This value is for inhalable dust containing no asbestos and < 1% crystalline silica			
glass, oxide, chemicals	65997-17-3	TWA (inhalable dust)	2 mg/m3	AU OEL
	Further information: Where almost all the airborne material is fibrous MMVF, an inhalable dust exposure standard of 2 mg/m3 (8 hour TWA) must also be applied to minimise mechanical irritation from largely non-respirable fibre. This inhalable standard is not to take precedence over the respirable fibre standard, where applicable. For those applications where MMVF is combined with other material such that the proportion of respirable fibres is extremely low or is difficult to measure because of the larger portion of non-fibrous MMVF material, it is appropriate to apply the exposure standard for nuisance dusts of 10 mg/m3, measured as inhalable dust (8 hour TWA), Category 1B (Carc. 1B) Presumed to have carcinogenic potential for humans, As described in IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Volume 81, Man-Made Vitreous Fibres, pp. 45-54, 2002, IARC Press, Lyon, France3, Any MMVF that meet the requirements of Note R in Regulation EC No. 1272/2008 page 353/335 are exempted from mandatory classification as a carcinogen under the GHS in the European Union.			
		TWA (Respirable)	0.5 fibres per millilitre	AU OEL
	Further information: Category 1B (Carc. 1B) Presumed to have carcinogenic potential for humans, As described in IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Volume 81, Man-Made Vitreous Fibres, pp. 45-54, 2002, IARC Press, Lyon, France3, Any MMVF that meet the requirements of Note R in Regulation EC No. 1272/2008 page 353/335 are exempted from mandatory classification as a carcinogen under the GHS in			

SAFETY DATA SHEET

PROHESIVE ULTRAPRO



Version 1.0

SDS Number: 100000013073

Revision Date: 30.05.2016

	the European Union.			
		TWA (inhalable dust)	2 mg/m3	AU OEL
	<p>Further information: Where almost all the airborne material is fibrous MMVF, an inhalable dust exposure standard of 2 mg/m3 (8 hour TWA) must also be applied to minimise mechanical irritation from largely non-respirable fibre. This inhalable standard is not to take precedence over the respirable fibre standard, where applicable. For those applications where MMVF is combined with other material such that the proportion of respirable fibres is extremely low or is difficult to measure because of the larger portion of non-fibrous MMVF material, it is appropriate to apply the exposure standard for nuisance dusts of 10 mg/m3, measured as inhalable dust (8 hour TWA), Category 2 (Carc. 2) Suspected human carcinogen, As described in IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Volume 81, Man-Made Vitreous Fibres, pp. 45-54, 2002, IARC Press, Lyon, France3, MMVF with random orientation, alkaline oxide and alkali earth oxide (Na2O+K2O+CaO+MgO+BaO) content greater than 18% by weight., Exempted are: - Any MMVF which have been tested according to the test protocol Methods for the Determination of the Hazardous Properties for Human Health of Man Made Mineral Fibres April 1999 and Note Q in EC Regulation No. 1272/2008 page 353/335 and found to comply with these tests. - Any MMVF that meet the requirements of Note Q in EC Regulation No. 1272/2008 page 353/335 are exempted from mandatory classification in the European Union as a carcinogen under the Globally Harmonized System for Classification and Labelling of Chemicals (GHS). Note IARC has classified mineral wools (glass wool, rock wool (stone wool), slag wool and continuous glass filament) as IARC Category 3: not classifiable as to carcinogenicity in humans. - Any MMVF that meet the requirements of Note R in Regulation EC No. 1272/2008 page 353/335 are exempted from mandatory classification as a carcinogen under the GHS in the European Union</p>			
		TWA (inhalable dust)	2 mg/m3	AU OEL
	<p>Further information: Where almost all the airborne material is fibrous MMVF, an inhalable dust exposure standard of 2 mg/m3 (8 hour TWA) must also be applied to minimise mechanical irritation from largely non-respirable fibre. This inhalable standard is not to take precedence over the respirable fibre standard, where applicable. For those applications where MMVF is combined with other material such that the proportion of respirable fibres is extremely low or is difficult to measure because of the larger portion of non-fibrous MMVF material, it is appropriate to apply the exposure standard for nuisance dusts of 10 mg/m3, measured as inhalable dust (8 hour TWA), Category 2 (Carc. 2) Suspected human carcinogen, As described in IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Volume 81, Man-Made Vitreous Fibres, pp. 45-54, 2002, IARC Press, Lyon, France3, MMVF with random orientation, alkaline oxide and alkali earth oxide (Na2O+K2O+CaO+MgO+BaO) content greater than 18% by weight., Exempted are: - Any MMVF which have been tested according to the test protocol Methods for the Determination of the Hazardous Properties for Human Health of Man Made Mineral Fibres April 1999 and Note Q in EC Regulation No. 1272/2008</p>			

SAFETY DATA SHEET
PROHESIVE ULTRAPRO



Version 1.0

SDS Number: 100000013073

Revision Date: 30.05.2016

	page 353/335 and found to comply with these tests. - Any MMVF that meet the requirements of Note Q in EC Regulation No. 1272/2008 page 353/335 are exempted from mandatory classification in the European Union as a carcinogen under the Globally Harmonized System for Classification and Labelling of Chemicals (GHS). Note IARC has classified mineral wools (glass wool, rock wool (stone wool), slag wool and continuous glass filament) as IARC Category 3: not classifiable as to carcinogenicity in humans. - Any MMVF that meet the requirements of Note R in Regulation EC No. 1272/2008 page 353/335 are exempted from mandatory classification as a carcinogen under the GHS in the European Union			
calcium carbonate	471-34-1	TWA	10 mg/m3 (Calcium)	AU OEL
	Further information: This value is for inhalable dust containing no asbestos and < 1% crystalline silica			
calcium sulfate	7778-18-9	TWA	10 mg/m3	AU OEL
	Further information: This value is for inhalable dust containing no asbestos and < 1% crystalline silica			

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : powder
- Colour : white
- Odour : characteristic
- Odour Threshold : No data available
- pH : No data available
- Melting point/range / Freezing : No data available

SAFETY DATA SHEET

PROHESIVE ULTRAPRO



Version 1.0

SDS Number: 100000013073

Revision Date: 30.05.2016

point	
Boiling point/boiling range	: No data available
Flash point	: No data available
Evaporation rate	: No data available
Flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: No data available
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Molecular weight	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions.
Conditions to avoid	: No data available
Incompatible materials	: No data available
Hazardous decomposition products	: No decomposition if stored and applied as directed.



SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

calcium sulfate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

SAFETY DATA SHEET

PROHESIVE ULTRAPRO



Version 1.0

SDS Number: 100000013073

Revision Date: 30.05.2016

Additional ecological information : There is no data available for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulation

IATA-DGR

Not dangerous goods

IMDG-Code

Not dangerous goods

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

Not dangerous goods

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform Scheduling of Medicines and Poisons : No poison schedule number allocated

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Prohibition/Licensing Requirements : There is no applicable prohibition or notification/licensing requirements, including for carcinogens under Commonwealth, State or Territory legislation.

The components of this product are reported in the following inventories:

AICS : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

SAFETY DATA SHEET

PROHESIVE ULTRAPRO



Version 1.0

SDS Number: 100000013073

Revision Date: 30.05.2016

Date format : dd.mm.yyyy

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy. MSDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.